## **COMBi-STE 5000-8000**




The multi-directional, electric, stand-on forklift designed for the safe, space saving and productive handling of long and bulky loads.














## **COMBi-STE** 5000-8000









| DEE | DESCRIPTION  | C5000                         | C6000      | C8000      |
|-----|--|-------------------------------|------------|------------|
| Ta  | Max. Lift Height                                     | C5000                         | 159"       | Caudo      |
| 1b  | Freelift Height                                      | 0"                            |            |            |
| 2   |  | 0<br>111½"                    |            |            |
| 3   | Height Mast Closed Max. (Mast raised)                | 204"                          |            |            |
| 4   | Overall Length                                       | 783/4"                        |            | 821/2"     |
| 5   | Mast Travel  | 51"                           |            | 02/2       |
| 6   | Ground Clearance Under Mast                          | 9"                            |            |            |
| 7   | Ground Clearance to Wheelbase                        | 6"                            |            |            |
| 8   |  | 1071/2"                       |            |            |
| 9   | Height Over Cab (without work lights) Platform Width | 104"                          |            | 1143/4"    |
| 10  | Outside Spread of Fork Arms                          | 451/4"                        |            | 53"        |
| 11  | Track Front  | 82"                           |            | 903/4"     |
| 12  | Frame Opening  | 481/2"                        |            | 59"        |
| 13  | Load Center Distance                                 | 231/2"                        |            | 37         |
| 14  | Overhang Front                                       | 91/4"                         |            |            |
| 15  | Wheelbase  | 621/4"                        |            | 68"        |
| 16  | Overhang Back  | 51/4"                         |            | 00         |
| 17  | Length From Face of Fork                             | 311/2"                        |            | 35½"       |
| 18  | Approach Angle                                       | 45°                           |            | 33/2       |
| 19  | Ramp Angle   | 17°                           |            |            |
| 20  | Departure Angle                                      | 45°                           |            |            |
| 21  | Forward Tilt   | 4°                            |            |            |
| 22  | Backward Tilt  | 4°                            |            |            |
| 23  | Minimum Outside Radius                               | 731/2" 783/4"                 |            |            |
| 24  | Platform Height                                      | 19"                           |            | 7074       |
| 25  | Platform Length                                      | 471/4"                        |            |            |
| 23  | Tration Length                                       |                               | 7774       |            |
| Α   | Capacity   | 5000 lbs                      | 6000 lbs   | 8000 lbs   |
| В   | Unladen Weight                                       | 14,010 lbs                    | 14,220 lbs | 14,661 lbs |
| C   | Maximum Ground Speed                                 | 6¼ mph                        |            |            |
| D   | Gradeability   | 10%                           |            |            |
| E   | Battery Capacity                                     | 72 V / 500 Ah                 |            |            |
| F   | Fork Section   | 2" x 5" x 47¼" 2" x 6" x 47¼" |            |            |
| G   | 16 / 12 - 10 Front Tire (Solid)                      | OD 16" / Width 10"            |            |            |
| Н   | 23 x 10 - 12 Rear Tire (Super Elastic)               | OD 22" / Width 8"             |            |            |
| I   | Standard Color                                       | Green & Gray                  |            |            |
| J   | AC Electric Traction Motor x 2                       | 72 V / 6.7 hp                 |            |            |
| K   | AC Electric Pump Motor                               | 72 V / 2.5 hp                 |            |            |



## Features Include:

- Rubber Mounted Cabin
- Multi-Directional Operation
- AC Motor Technology
- Load Sensing Steering
- 2 Wheel Electric Drive
- Stand-up Operator
- (Sit Down Cabin Option Available)
- Adjustable Guide Rollers

## **Distributed by:**

PCT Patent Application No. PCT/EP2014/053066; UK Patent Application No. GB1302811.3

COMBILIET HAS A POLICY OF CONTINUOUS PRODUCT DE VELOPMENT AND RESERVES THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE. SPECIFICATIONS AND/OR DIMENSIONS MAY VARY FROM THOSE ILLUSTRATED IN SOME COUNTRIES